

~~DaimlerChrysler AG~~

IP20 Rec'd PCT/PTO 01 SEP 2006

~~Safety device for a motor vehicle~~  
SAFETY DEVICE FOR A MOTOR VEHICLE

5

BACKGROUND AND SUMMARY OF THE INVENTION

This application is a National Phase of  
PCT/EP2005/002062, filed February 26, 2005, and claims  
10 the priority of DE 10 2004 010 542.1, filed March 4,  
2004, the disclosures of which are expressly incorporated  
by reference herein.

The present invention relates to a safety device for a  
motor vehicle comprising at least one closable opening of  
15 the interior ~~according to the precharacterizing clause of~~  
~~Patent Claim 1.~~

DE 40 31 552 A1 discloses a safety device for a vehicle,  
the interior of which has at least one opening, for  
20 example a side window, which can be closed or opened,  
according to choice, by a closing element coupled to a  
servo drive. A sensor system senses the vehicle  
deceleration in the traveling direction and, if a default  
value for the vehicle deceleration is exceeded, initiates  
25 the closing movement of the closing element. Given  
suitable selection of the default value for the vehicle  
deceleration, the opening can already be closed before  
the motor vehicle hits an obstacle. If an accident  
actually occurs, the occupants of the vehicle are  
30 protected from injuries caused by foreign bodies entering  
the vehicle from the outside through the opening. It is  
similarly possible to avoid occupants of the vehicle  
being thrown out through the opening.

DE 101 21 386 C1 describes a method for activating a reversible occupant protection means in a motor vehicle with a sensor system sensing driving state data.

5 Instances of emergency braking, oversteering and understeering of the motor vehicle are monitored as driving state data. On the basis of such a state, the occupant protection means is triggered. The driving state data can also be used to determine the direction  
10 from which the greatest danger is to be expected. The occupant protection means is activated in such a way that the protective effect is provided in accordance with the direction of greatest danger.

15 Furthermore, DE 44 11 184 C2 discloses a restraining belt system for a seat in a vehicle, comprising a seat belt and a belt tensioner for securing a passenger on the seat. The device determines the distance from an object and the corresponding relative velocity. This can be  
20 used to determine the expected time to a possible collision between the vehicle and the object. A control unit generates a control signal, which increases the force of the belt tensioner at an appropriate time before the possible collision. If a collision can be avoided,  
25 the force of the belt tensioner is reduced again. The controllable belt tensioner is configured as a pretensioner, which before the collision is active only up to a predetermined pretension, a further belt tensioner being triggered for tighter tensioning of the  
30 seat belt if the collision is actually found to have occurred.

[[The]] An object of the present invention is therefore  
~~based on the object of providing to provide~~ a safety  
35 device for a motor vehicle comprising at least one closable opening of the interior, with a closing element driven by a servo drive being provided for closing the

opening, which device has improved occupant protection in comparison with ~~[[the]]~~ known safety devices ~~that are known from the prior art.~~

5 The ~~stated~~ foregoing object is achieved by a safety device for a motor vehicle comprising at least one closable opening of the interior ~~with the features of Patent Claim 1~~ in which a control unit evaluates the data relevant to safety when the vehicle is in motion and  
10 activates the servo drive at such a time that the closing element is moved from an open position in the closing direction into a predetermined position, in which the closable opening has an open gap, prior to the occurrence of an expected accident.

15 According to the present invention, the control unit evaluates the data relevant to safety when the vehicle is in motion and activates the servo drive at such a time that the closing element for closing the opening is moved  
20 into the predetermined position, in which the closable opening has an open gap, prior to the occurrence of an expected accident. The safety device for the motor vehicle comprises at least one closable opening of the interior of the motor vehicle, the closing element that  
25 is driven by the servo drive being provided for closing the opening, and the control unit.

The safety device according to the invention ensures that, in the event of an accident occurring, adequate  
30 oxygen is supplied and made available to the occupants of the motor vehicle. In the event of an accident, there may be high levels of contamination from gas or soot particles, for example as a result of pyrotechnic occupant protection ~~[[means]]~~ device being triggered,  
35 representing a high degree of risk to the health of the occupants. The opening, left open by a gap, for example a side window, allows the gas or soot particles to escape

from the interior of the motor vehicle into the surroundings and at the same time allows oxygen to be supplied from the outside to the occupants in the interior. In this case, it is ~~of advantage~~ advantageous that the closing element can be moved into the predetermined position both from an open position and from the closed position. The predetermined position for the closing element is already reached before the occurrence of the actual accident, thereby achieving additional safety for the occupants.

Movement of the closing element into the predetermined position while the accident is actually in progress could no longer occur under some circumstances, on account of failure of the voltage supply. The time immediately before the accident is used to initiate precautionary measures to improve occupant safety. The safety device acting with a preventive effect ensures preventive occupation protection.

The closing element may be any automatically closable component of the motor vehicle, for example a windowpane or a sliding roof.

The data relevant to safety when the vehicle is in motion may be, in particular, driving state variables. Variables such as vehicle speed, yaw, longitudinal and lateral accelerations, brake pedal and gas pedal positions and the steering angle may be used as driving state variables. Furthermore, the status of operating elements such as turn indicators and hazard warning lights as well as the status of sensors and control devices concerning the motor vehicle may also be used.

As an alternative or in addition, the data relevant to safety when the vehicle is in motion may be ambient data. Ambient data is the term used to refer to data provided

by ambient sensors, telematic systems and communication of the motor vehicle with other motor vehicles and stationary communication systems. Examples of ambient data are information on the current location, on the category of road and on the lane in which one's own motor vehicle is driving. Other ambient data include the state of the road, temperature, weather, light conditions and the speed, distance, type and size of motor vehicles and other road users ahead, alongside, following or oncoming.

It is ~~of advantage~~ also advantageous if the data relevant to safety when the vehicle is in motion are evaluated driver activities. Sensing driver activity comprises, for example, detecting eye movement and viewing direction, but also operating actions on operating elements ~~[[,]]~~ such as, for example, the steering wheel, gear selector lever and brake pedal. By evaluating a ~~plethora of~~ safety-relevant data ~~it is possible if need be for~~ the correct point in time for closing the tilting roof ~~[[to]]~~ can be determined, if need be, by means of the control unit.

~~Further advantageous refinements of the invention are provided in the subclaims.~~

Other objects, advantages and novel features of the present invention will become apparent from the following detailed description of the invention when considered in conjunction with the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

~~The invention is explained in more detail on the basis of an exemplary embodiment in the single sole figure, the figure showing is a schematic showing of a detail of a~~

safety device for a motor vehicle comprising at least one closable opening of the interior ~~in a block diagram~~.

#### DETAILED DESCRIPTION OF THE DRAWINGS

5 According to the sole figure, a safety device designated  
generally by numeral 1 for a motor vehicle ~~comprises~~  
includes a closable opening of the motor vehicle interior  
2. ~~A of the motor vehicle,~~ a closing element 4 driven by  
a servo drive 3 ~~[[being]]~~ is provided for closing the  
10 opening.

A control unit 5 evaluates the data 6 relevant to safety when the vehicle is in motion and activates the servo drive 3 at such a time that the closing element 4 is  
15 moved into a predetermined position, in which the closable opening has an open gap, prior to the occurrence of an expected accident. The closing element 4 can be moved into the predetermined position both from an open position and from the closed position. The closing  
20 element 4 may be configured, for example, as a side window or as a sliding roof of the motor vehicle.

The servo drive 3 may additionally have a quick closing function, which is activated when the servo drive 3 is  
25 activated by the control unit 5. The quick closing function of the servo drive 3 ensures that the closing element 4 has reached its end position with the open gap at an appropriate time before the occurrence of the actual accident. The quick closing function may also be  
30 realized in a separate servo drive 3. If the accident does not occur, the closing element 4 is returned again to its starting position.

The size of the gap can be individually preset, depending  
35 on the configuration of the closing element 4. The presetting may take place at the factory or be performed by an occupant of the motor vehicle.

The safety device 1 may also activate a number of closing elements 4, for example a number of side windows of the motor vehicle. The activation of the side windows may  
5 take place in various operating modes. In a first operating mode, all the side windows can be moved into a predetermined position at the same time. In a second operating mode, only the windows that are next to an occupant are activated. Occupant sensing may be carried  
10 out by [[means]] way of a seat occupancy detection. Other operating modes for the safety device 1 are also ~~conceivable, however~~ contemplated as within the scope of the present invention.

15 The data 6 relevant to safety when the vehicle is in motion are driving state variables, ambient data and/or evaluated driver activities.

The safety device 1 according to the present invention  
20 for the motor vehicle ~~comprising~~ having the closable opening of the interior 2 ensures a secured supply of oxygen to the occupants of the motor vehicle during and after an accident. The safety device 1 can be ~~realized~~ implemented with little expenditure, [[since]] because  
25 the main components of the safety device 1 are generally already integrated in the motor vehicles as standard items.

1 / 1

